



## PROTECTION BACHAYE AAPKI REPUTATION



WARRANTY BOOKLET




Warranty ID. No.





# SEEP GUARD HORIZONTAL SURFACES





### WARRANTY CERTIFICATE FOR BIRLA WHITE SEEP GUARD HORIZONTAL SURFACES

Birla White, a unit of Ultra Tech Cement Limited, (referred to as "Company") offers an Eight Year Warranty from the date of purchase, on the application system for its product Birla White SEEP GUARD Horizontal Surfaces (hereinafter referred to as "Product") on Roofs & Terraces/Horizontal Surfaces. SEEP GUARD Horizontal Surfaces' application should be as mentioned in the "Application Process" section of this document. SEEP GUARD Horizontal Surfaces comes with the triple promise of outstanding tensile adhesion, enhanced flexibility and excellent crack bridging properties.

### **WARRANTY COVERAGE**

- 1. SEEP GUARD Horizontal Surfaces offers an Eight Year Waterproofing Warranty on the Coating Failure (defined hereinafter).
- 2. It covers the priming coat & two-coat application of the SEEP GUARD Horizontal Surfaces over fresh & existing RCC/concrete/cementitious surfaces.
- 3. Application areas:
  - a. Building roof, Terrace, Parapets
  - b. Sloping roofs and Chajjas
- 4. Entire terrace along with parapet needs to be enveloped as recommended.

### **WARRANTY ENROLMENT PROCESS**

- 1. Within 30 days of purchase, the warranty must be registered with the company by contacting the Birla White Toll-Free Helpline at 1800-111-717 or using the online warranty registration link given on the Birla White website.
- 2. The customer should note down the batch number and production date from the Product package at the time of purchase.
- 3. The product name, quantity, and purchase date should all be clearly stated on the purchase invoice.
- 4. The customer is required to furnish the details as to his Name, Contact Details, Mobile No., details of the product purchased, Bill no., Dealer details, etc., during warranty registration.
- 5. The customer shall receive a unique warranty no. against their registration.

### **COMMENCEMENT AND DURATION**

- 1. The warranty benefit commences from the date of purchase ("Commencement Date") of SEEP GUARD Horizontal Surfaces. It covers its application on fresh & existing RCC/concrete/cementitious surfaces.
- 2. On both fresh & existing RCC/concrete/cementitious surfaces where SEEP GUARD Horizontal Surfaces has been applied, the warranty shall be applicable for Eight (8) years.
- 3. If a claim occurs during the warranty period, the warranty will only be valid as of the original purchase date, and even if the claim is settled, the warranty's commencement date will always remain that date.

### **EXTENT OF WARRANTY APPLICABILITY**

- 1. For the warranty to be applicable:
  - a. The total volume of the SEEP GUARD Horizontal Surfaces purchased exceeds 45 Kgs and upto 200 Kgs.
  - b. If the quantity of SEEP GUARD Horizontal Surfaces coating required for a particular site exceeds 200 KGs, a representative from the Company will conduct a preliminary inspection of the surface to be coated. If the inspection reveals any issues that do not meet the required standards, appropriate corrective actions will be recommended.
- 2. It is mandatory that only this product has to be used exclusively on the entire site for which warranty is registered/claimed, i.e., no warranty will be registered/claim will be entertained where any other brand of Waterproofing has been used for a similar application in different areas of one site even if minimum purchase quantity mentioned above has been purchased and used in a part area of one site.
- 3. Recommended forced system coverage of 1.11 Sq. mt./L (12 Sq. ft./kg) must be achieved for warranty registration.
- 4. The warranty may be registered when the customer purchases the minimum quantity of product mentioned above in more than one lot and on different days but within 30 days from the date of the first purchase of the product for a particular site.
- 5. The product should be applied within one month from the date of purchase or within nine months starting from the date of manufacture of the product, whichever is earlier.
- 6. Throughout this warranty, the word "Coating Failure" is directly attributable to deficiencies in the product's application. It shall mean any of the following occurring, subject to the other conditions laid down under this warranty:
  - a. Failure of waterproofing, viz., water ingress through the Coatings in roof.
  - b. Film integrity, flaking and peeling of SEEP GUARD Horizontal Surfaces caused by one coat of the product coming off from another coat or both the coats coming off from the substrate
  - c. The coating film shows blistering, splits, tears, cracks, or shows evidence of excessive weathering due to defective material.
  - d. Growth of fungus and algae on terrace surfaces\* (at least spread over a minimum area of 10 sq. ft.).

### **APPLICATION PROCESS**

### Instructions for Use/Application of the Product

- SEEP GUARD Horizontal Surfaces has to be used on fresh & existing RCC/concrete/cementitious surfaces.
- b. All elements of surface preparation before the application and during application work have to be by the instructions provided for SEEP GUARD Horizontal Surfaces, as detailed in this section below.

<sup>\*</sup>Please Note: The warranty is for eight (8) years only from the date of purchase (as per the purchase invoice).

### This warranty shall only be considered if the below-mentioned application procedure is followed:

### **Prior Check Before Product Application**

- 1. Before SEEP GUARD Horizontal Surfaces' application, it is essential to ensure that the substrate shall have no chalking problem, loose sand, or paint particles and be free from oil and grease stains. For new plaster, the substrate shall be cured entirely, crack-free, and in sound condition.
- 2. Any active source of dampness/leakage needs to be treated before applying SEEP GUARD Horizontal Surfaces.
- 3. New masonry surfaces must be cured entirely for the best results. It is highly recommended to allow 28 days as curing time for new masonry surfaces.
- 4. Ensure that surface is entirely free from all dirt, powdery residue, loosely held plaster, grease, oil, or any other contamination. Any previous growth of fungus, moss, or algae needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- 5. Surface cracks must be filled (<3mm) by crack filler products & bigger cracks, damaged portion and hollow areas must be repaired by Birla White Levelplast (polymer cement modified mortar product) as per the instructions in its leaflet.
- 6. In case of efflorescence, surface should be clean thoroughly to remove all loose particles from the surface.
- 7. Suitable slope is provided to the roof to avoid water ponding.
- 8. Loose plaster, structural cracks are repaired as per standard construction practices.
- 9. Previous water proofing treatment (2k cement based/ bituminous etc.) if any to be completely removed to reach bare plaster.
- 10. It is recommended to cover the entire roof/terrace along with parapets till height of 2 feet below the terrace parapet joint with SEEP GUARD Horizontal Surfaces. In case of adjoining terraces (separated by a common parapet wall), the terrace not coated with SEEP GUARD Horizontal Surfaces must not have any leakages.

### **Product Application Process**

- 1. Preparation of the substrate surface
  - Remove all the loosely adhering material like, dirt, dust, organic solvent (de-shuttering/curing free compound) & oil etc. from the surface by using emery paper, chisel or wire brush, etc.
  - Wash the surface properly with clean water & allow the surface to dry completely before application of SEEP GUARD Horizontal Surfaces.

### 2. Priming Coat

- Mixing ratio (1:1): Slowly add 1 kg of SEEP GUARD Horizontal Surfaces with 100% clean water (1 Kg SEEP GUARD Horizontal Surfaces + 1000 ml water) to make a homogeneous slurry.
- Mixing of the product with water should be carried out by preferably mechanical stirrer (3-5 minutes) or using a metallic rod (5-10 minutes) to obtain a creamy consistency.

- Leave the slurry for 5 minutes after thorough mixing to get best performance & release entrapped air during prepared slurry should be used within 1-1.5 hours.
- Apply SEEP GUARD Horizontal Surfaces priming coat on the clean & dry wall/substrate surface uniformly with the help of painting brush or roller.
- Allow the surface to dry for at least 4-6 hours after priming coat.

### 3. First & Second Coat

- Slowly add 1 kg of SEEP GUARD Horizontal Surfaces with 60-65% clean water (1 Kg SEEP GUARD Horizontal Surfaces + 600-650 ml water) to make a homogeneous slurry.
- Mixing of the product with water should be carried out by preferably mechanical stirrer (3-5 minutes) or manually (5-10 minutes) to obtain a creamy consistency. Prepared slurry should be used within 1-1.5 hours.
- After thoroughly mixing, apply two coats of SEEP GUARD Horizontal Surfaces in interval of 4-6 hours with the help of a painting brush/appropriate roller.
- The direction of the brush/roller movement should only be horizontal for first coat and vertical for 2nd coat or vice versa. This will help in getting a better surface finish.
- Leave the surface to dry completely (preferably 10-12 hours).
- For best performance on terrace, ensure that the product is applied on the entire roof including parapet wall. The total thickness of both the coats should be limited to maximum 1.5 mm.

### Do's and Don'ts -

- 1. Ensure that during application substrate must be in proper clean & dry condition.
- 2. Mixing is very important & hence utmost care is to be taken for proper & thorough mixing with hand or mechanical stirrer to get the desired best results. Mixing is to be continued till a uniform slurry is formed.
- 3. Only a required quantity of mix should be prepared which can be used within 1-1.5 hours.
- 4. Ensure loosely adhered/dirt free wall surface.
- 5. Surface should clean before application of product for better bonding & coverage.
- 6. Store in a cool & dry place.
- 7. Wear safety goggles during application. In case of contact with eyes rinse immediately with plenty of water & seek medical advice.
- 8. Keep it out of reach of children.
- 9. It is recommended to wear suitable eye & nose mask protection during surface preparation & product application.
- 10. Avoid application of the product in afternoon when temperature is high.
- 11. Whenever the surface temperature exceeds 35°C, the product should not be used.
- 12. While preparing the mix, SEEP GUARD Horizontal Surfaces should be added to water and not vice versa.

### **WARRANTY LIABILITY**

1. Over the warranty period, the company's responsibility will shrink according to the following scale:

Within the first 12 months after the commencement date	100% of replacement cost
From month 13 to month 36 after the commencement date	75% of replacement cost
From month 37 to month 60 after the commencement date	50% of replacement cost
From month 61 to month 96 after commencement Date	25% of replacement cost

- 2. The company's responsibility will be limited to the purchase price of the product.
- 3. The company will only replace the SEEP GUARD Horizontal Surfaces where failure has occurred in accordance with the liability.
- 4. The company will only provide replacement product for re-application of coating, as it may be necessary to set right the "Coating Failure" in the affected portion only in accordance with the liability.
- 5. The company will entertain the warranty claim only once during the warranty period for the area of application, i.e., if the warranty claim is registered again for a particular area of the site during the warranty period, no further claim will be entertained by the company for that area.

### **WARRANTY EXCLUSIONS**

- 1. The warranty shall be void/ null in the following events:
  - a. Intermittent dripping of water due to proximity of vegetation or air-conditioning units or any other sources of water leakage like potted plants, plants, plumbing lines, broken water spout, or water flow from overhead tank, etc.
  - b. De-bonding of the base (material used for levelling) from the surface & cracks formation on the same.
  - c. Water ingress from areas not coated with SEEP GUARD horizontal surfaces.
  - d. Inadequate maintenance of the roof leading to water logging.
  - e. Growth of algae or fungus on surfaces other than masonry walls.
  - f. Defects in the design of the building or roof design, including inadequate sloping, sub-optimal number of drainages, settlement, movement or other structural defects.
  - g. Exposure of the applied coating to damaging substances such as chemicals, solvents or oils.
  - h. Building or structural changes carried out after the coating has been applied.
  - i. Leaks or damages due to any additional installations on the coated surface or usage on the surface of pre-installed elements that is not consistent with recommended application.
  - j. Surface exhibit plaster, screed failure or de-bonding of base (material used for levelling) from the surfaces and crack formation on the same.

- k. Puncturing of cured coating due to sharp objects, movements of heavy articles, fixing of antenna or other structures on the terrace.
- I. SEEP GUARD Horizontal Surfaces is not consumed within 30 days of the date of purchase or within one year starting from the date of manufacture of the product, whichever is earlier.
- 2. The Warranty will not cover any defects arising out of factors out of control of the Company, including but not limited to:
  - a. Coating failures due to structural defects, moss and other vegetative growth, continuous dampness of the surface, staining due to plant pots, efflorescence, waterlogging/stagnant water.
  - b. There is a reduction of Gloss/Sheen/Ageing which is part of weathering process.
  - c. Natural calamities such as earthquakes, cyclones, and flooding.
  - d. Failure or defects in the structure or previous coating, or any repair work undertaken.
  - e. Vandalism, accidents and fire.
  - f. Abuse by the customer.
  - g. Causes other than defects in SEEP GUARD Horizontal Surfaces.
  - h. Improper surface preparation.
  - i. Surface with contaminants.
  - j. Wilfully inflicted damage.
  - k. Any act or omission by the Painter/Contractor/Applicator caused the SEEP GUARD Horizontal Surfaces to be defective.

### **CLAIMS AND REPAIRS**

- 1. Any claims made in terms of this warranty shall be made within 30 days of the consumer discovering any defect, damage, or failure.
- 2. The consumer shall immediately apprise the Company of the claim through the Birla White Toll-Free Helpline (1800-111-717) by furnishing full details thereof and shall set out the basis on which they believe that the Company is liable with respect to the warranty offered.
- 3. The company, at its own discretion, may appoint a technical person to inspect and validate the application process followed as per the directions specified.
- 4. On receipt of such information, the authorized officers/representatives of the Company will ensure an inspection of the site where the Coating Failure has been reported and prepare an inspection report in the format prescribed by the Company. It shall be mandatory for the Company's authorized representative and the customer to sign the inspection report. The authorized representative of the Company shall submit the inspection report to the company. The quantity of the product to be given to the customer under the terms of the warranty for the area of the Coating Failure as determined by the Inspecting team of the Company shall be final.
- 5. The Company, on receipt of the inspection report, may pass/reject the claim as per findings in the report and terms of the warranty.
- 6. The Company may conduct as many inspections from any of its officers/representatives as it may deem fit to settle the claim. Before such inspection or testing, the consumer shall not be entitled to perform any repairs or remove or tamper with any part of the system.

- 7. The customer or his employees/relatives/any other person(s) relating to customer or any third party shall never restrain the authorized representatives of the Company from entering the site and shall never indulge in any fight or quarrel or arguments with the authorized representatives of the company visiting the site for any purpose.
- 8. The Company shall deploy its best endeavours to ensure that product required for repair is made available as soon as possible at the site/place where the repair needs to be carried out but does not assume any liability for delay in this respect.
- 9. The company's liability concerning the warranty on the product shall be limited to making available the product at site only. It shall not include labour costs or other material used for re-application.
- 10. Required quantity of the product will be made available to the customer via the same dealer from whom the initial purchase was made.
- 11. The Company, in its sole discretion, shall be entitled to:
  - a. Ask company technical representative to monitor re-application. which is to be carried out in accordance with all its specifications and instructions.
  - b. We recommend that the customer appoint the contractor.

### **TERMS & CONDITIONS**

- 1. The warranty is applicable throughout India.
- 2. The product is to be purchased from authorized dealers/stockists of the Company against sale bills as required under GST laws/other statutory laws. The customer must keep the original invoice(s) for registering claims in the future if needed.
- 3. The warranty must be registered by the customer with the Company as per the procedure mentioned in this document.
- 4. The product must be stored as specified in its packaging instructions and used within its shelf life.
- 5. SEEP GUARD Horizontal Surfaces should be applied as per the application instructions given in this document's 'Application Process' section and with good working practice. Warranty is applicable only if the application system defined above in section "Warranty Coverage" is followed.
- 6. Warranty is applicable only if the product had been applied on the entire affected wall. It is not relevant for localized patch applications.
- 7. SEEP GUARD Horizontal Surfaces should not be used in combination with products from any other manufacturer or any other intermediate product.
- 8. Regardless of anything stated in this clause, the customer's only recourse is this warranty; no other express or implied warranties are offered. It is expressly stated that the Company's liability shall be limited to the aforementioned obligations and that the Company shall not be liable for any incidental, indirect, or consequential damages or for any loss of revenue, profits, or contracts, whether resulting from contract violations, negligence, torts, or other causes.
- 9. If any dispute emerges between the Company and the customer regarding the above warranty, the arguments will be settled through mediation as per an alternate dispute resolution mechanism.

- 10. If for any reason, such dispute cannot be resolved amicably by the parties through a mediation process, then the same shall be referred to a sole arbitrator, to be appointed by mutual consent of both the parties, who shall resolve the dispute in accordance with the Arbitration and Conciliation Act, 1996 or any subsequent enactment or amendment thereto (the "Arbitration Act"). The decision of the arbitrator shall be final and binding upon the parties. The venue of the arbitration proceedings shall be Mumbai only. The language of the arbitration proceedings and the award shall be in English.
- 11. In case of any disputes, the same is subject to the exclusive jurisdiction of the courts of Mumbai.
- 12. Both the Customer and the Company will keep the facts and all things relating to any dispute confidential at all times.

PRODUCT DETAILS	
Purchase Date	
Purchase Invoice No.	
Quantity in Bags	
Mfg. Date	
DEALER DETAILS	CONTRACTOR DETAILS
Name	_ Name
Phone No.	_ Phone No
USER DETAILS	
Name	
Phone No.	
Email id	
Site Address	
State	
City	
Pincode	

### **NOTES**





## **Birla White - A Unit of UltraTech Cement Limited**