

# ZYPCOTE

Birla White Zypcote is specially formulated gypsum plaster for internal plastering. It can be applied as a replacement of traditional cement. It can also be used as levelling material. Zypcote's additives give it great compressive strength while being light weight.

It does not require water curing which makes the surface ready for painting in 72 hours.



## PRODUCT HIGHLIGHTS



No Water Curing



Shrinkage Crack Resistant



Easy to Apply



Economical & Value for Money

## GALLERY



## FEATURES

- Green building product.
- Higher Coverage & Economical
- Can be applied in thicker coat 0.008-0.01 meter thickness
- No curing
- Shrinkage crack resistant

## BENEFITS

- Easy to apply just add water
- Achieve perfect corners and level finish on your walls with minimal effort.
- Better acoustic & insulation properties than cement sand plaster
- No curing is required and surface is ready within 72 hours for painting

## TECHNICAL SPECIFICATIONS

Technical Parameter	Birla White Zypcote
Dry bulk Density kg/m <sup>3</sup>	645-770
Initial Setting Time in Minutes	15-25
Final Setting Time in Minutes	20-30
Approximate Coverage* in square meter	≥ 80
Soluble MgO Wt%	As per IS code 2547 Part II
Soluble Na <sub>2</sub> O wt%	As per IS code 2547 Part II

## AVAILABLE SIZES

25Kg



SCAN TO KNOW MORE

